

FUZZYSCAN PA670BT HC

Rugged 2D Pocket Scanner



Rugged 2D pocket scanner for hygiene-sensitive applications

Equipped with a disinfectant-ready enclosure, the PA670BT HC is ideal for use in hygiene-sensitive environments such as hospitals, clinics, pharmacies, laboratories, and food processing plants. This 2D barcode scanner leverages the cordless technology of Bluetooth to enable superior mobility. The PA670BT HC fits easily inside a pocket, but can also be carried with a lanyard for quick access. Its over-mold enclosure offers IP65-level protection, and is built to withstand 2-meter falls onto concrete.

- Disinfectant-ready enclosure with antimicrobial additives
- Compliance with JIS Z2801 : 2000 antimicrobial standard
- Pocket-size and easy to carry
- IP65 level protection against dust and water
- Wireless range of up to 100m with smart cradle or dongle
- Works with various Android and iOS devices
- Batch Scanning for simple stocktaking
- Reads most challenging and problematic barcodes
- Reads electronic barcodes from digital screens
- Withstands 2-meter drops onto concrete
- Integrated vibrator for tactile confirmations
- Supports multilingual data output
- Single scan configuration with the iCode

Sanitation-Friendly

Disinfectant-ready enclosure

The PA670BT HC's housing is disinfectant-ready and can be wiped down with Cino's recommended cleaning solutions.

Inclusion of antimicrobial additives

Its housing's plastic material also incorporates a silver inorganic antimicrobial agent that will not wear off during its lifetime. This provides an extra layer of protection against the growth of microorganisms.

Compliance with antimicrobial standard

The PA670BT HC complies with the JIS Z2801:2000 antimicrobial standard. It is ideal for industries where the cleanliness of work tools is prioritized, such as healthcare or food processing.

Durable and ergonomic

This barcode scanner blends durability and ergonomics. Its over-molded enclosure offers IP65-level protection, as well a drop resistance of 2 meters. Furthermore, the PA670BT HC's handle is ergonomically designed to deliver a natural and comfortable grip all shift long.

Scan All Your Needs

Ready for challenges

Empowered by the FuzzyScan imaging platform, the PA670BT HC captures a vast array of problematic barcodes that are encountered in practice. For example: distorted, low contrast, dirty or damaged barcode labels, and electronic coupons on digital screens with poor lighting.

- Advanced data processing with DataWizard Premium
- Cost-free security with Security Plus



Great Portability



Hospital



Laboratory

Different solutions for different needs

The Standard-Range model is designed to fulfill the vast majority of retail scanning requirements. It offers swift readings on both regular and high-density barcodes, making it an excellent choice for general applications.

To help you capture those very high-density 2D barcodes that appear on jewelry tags or electronic components, Cino offers a specialized High-Density model.

Freedom of Cordless Scanning

Instant cordless migration

The PA670BT HC can be paired with Cino's smart cradle or smart dongle. These accessories offer a cordless working distance of up to 100 meters, and serve as instant wireless solutions for hosts that lack Bluetooth capabilities. Under PICO mode, the smart cradle and smart dongle can each support 7 scanners simultaneously, allowing users to centralize their data transmissions for better management.

Various connection possibilities

Furthermore, the PA670BT HC is also compatible with a wide range of Bluetooth-enabled hosts and operating systems. It can be easily paired with tablets or mobile phones running Windows, Linux, Android, or iOS through various link modes. The scanner can also be connected to different host interfaces, such as USB or RS232.

Comprehensive Functionalities

Real-time data transmissions

Under Online Scanning mode, the PA670BT HC will send captured data to its host device immediately after each scan. If the Out-of-range scanning function is enabled, up to 5,000 scans of EAN barcodes can be retained in your scanner when radio connection with the host device is lost.

Efficient stocktaking

Batch Scanning mode can be selected for inventory work. Barcode data is held in memory after each scan, and will be sent as a batch when transmission is activated. 100,000 scans of EAN barcode can be stored. Quantity value and time-stamp may be added to data immediately following capture.

Data validation made easy

Validation Scanning mode enables the scanner to record master data, and compare it against information that is subsequently captured. Should they not be a match, warning beeps will be emitted. This mode is useful for data validation tasks, such as shipping & receiving, and order picking.

Power that lasts

The PA670BT HC integrates an advanced power management system which maximizes the number of scans per charge. A full charge may be sufficient for a whole day's work or more. Battery status can be obtained simply by scanning the relevant command barcode. These features will help you focus on the tasks at hand, instead of the next recharge.



Pharmacy



Food Processing

Enhanced User Experience

Sharp aiming

The PA670BT HC's sharp LED beam helps user aim with greater speed and accuracy.

Clear feedback

Its loud beeper and multicolor LED lights are designed to provide clear status information.

Integrated vibrator

An integrated vibrator is available to deliver tactile confirmations when such silent signals are preferred.

Value Beyond Measure

DataWizard Premium

DataWizard Premium is a unique feature designed for FuzzyScan barcode scanners, enabling them to perform advanced data formatting and complex data processing. Costly or time-consuming changes to your host application can thereby be avoided. Beeping and LED indications can also be programmed through DataWizard Premium.

iCode, single scan setup

The iCode is a macro command barcode designed to streamline your setup process. Instead of scanning multiple command barcodes to configure their devices, users can easily generate a single iCode that contains all of the relevant parameters. Your entire setup can thus be completed with one quick scan. This simplified procedure lowers the risk of configuration errors, accelerates deployments, and reduces field service expenses.

Multilingual Edge, no more language barriers

With Cino's Multilingual Edge, FuzzyScan 2D scanners can be configured to output multiple languages, including Arabic, German, Greek, Russian, Turkish, etc. They can also be set to transmit Asian languages such as simplified Chinese, traditional Chinese, Japanese and Korean. The Multilingual Edge feature enables users to communicate without linguistic barriers, expanding business horizons.

Smart Scenes, easily adapt to diverse applications

Just like scene modes on digital cameras, the Smart Scenes feature minimizes configuration efforts by allowing you to choose from an assortment of settings tailored to particular scenarios. Simply pick the scene option that best suits your needs, and start scanning! Smart Scenes empowers you to attain exceptional scanning results with minimal efforts.

Security Plus, cost-free business protection

Security Plus guards your host application by restricting its access to authorized FuzzyScan barcode scanners only. Thanks to this security mechanism, developers can set their host applications to work exclusively with scanners containing an algorithm that they have pre-defined. Scanners lacking that customized algorithm will be denied access. Security Plus is available free of charge, delivering an easy and secure solution that protects businesses at no extra cost.

SPECIFICATIONS

Performance Characteristics

| | |
|----------------------------|---|
| Scan Pattern | Area Image |
| Print Contrast | 20% minimum reflectance difference |
| Light Source | Aiming Pattern : 630nm LED Illumination : 630nm LED |
| Min. Resolution | SR Model 3.3 mil Code 39 7 mil DM HD Model 2.7 mil Code 39 5 mil DM |
| Reading Range ¹ | SR Model 5 mil (0.13mm) C39 4~15 cm (1.5"~5.9") 13 mil (0.33mm) UPC/EAN 3~38 cm (1.1"~15.0") 10 mil (0.25mm) DM 3~15.5 cm (1.1"~6.1") HD Model 3 mil (0.07mm) C39 3~8 cm (1.1"~3.1") 5 mil (0.13mm) C39 3~11 cm (1.1"~4.3") 13 mil (0.33mm) UPC/EAN 2.5~16.5 cm (0.9"~6.4") 5 mil (0.13mm) DM 3.5~9 cm (1.3"~3.5") 10 mil (0.25mm) QR 3.5~8 cm (1.3"~3.1") |
| Roll, Pitch, Skew | Roll: 360°; Pitch: ± 75°; Skew: ± 65° |
| User Interface | 4 function keys, one scan button LEDs for power, link and status indication Adjustable beeper Optional vibrator |
| Data Processing | DataWizard Premium |
| Image Capture | Graphic Format: BMP |

Electrical Characteristics

| | |
|---------------------|--|
| Battery | Standard 3.7V, 1150mAh Li-ion rechargeable battery Optional 3.7V, 2300mAh Li-ion rechargeable battery |
| Battery Charge Time | Approx. 3-4 hours per full charge (Standard Battery) |

Communication Characteristics

| | |
|---------------------|---|
| RF Standard | Bluetooth v4.0 |
| RF Frequency Band | 2.402~2.4830 GHz unlicensed ISM band |
| Radio Link Modes | PAIR, PICO, SPP, HID |
| Communication Range | Up to 100m in open space with Smart Cradle or Smart Dongle, line of sight |
| Supported Profiles | SPP, HID |
| Supported Mobile OS | iOS (HID), Android (SPP & HID) |

Physical Characteristics

| | |
|------------|---|
| Dimensions | 119.0 mm (L) x 49.0 mm (W) x 24/38 mm (D) |
| Weight | 135g (Battery included) |

Supported Symbolologies

| | |
|-----------------|--|
| 1D Linear Codes | Code 39, Code 39 Full ASCII, Code 32, Code 128, GS1-128, Codabar, Code 11, Code 93, Standard & Industrial 2 of 5, Interleaved & Matrix 2 of 5, IATA, UPC/EAN/JAN, UPC/EAN/JAN with Addendum, Telepen, MSI/Plessey & UK/Plessey, GS1 DataBar, Linear & Linear Stacked |
| 2D Codes | PDF417, Micro PDF417, Codablock F, Code 16K, Code 49, Composite Codes, DataMatrix, MaxiCode, QR Code, MicroQR, Aztec |
| Postal Barcodes | Australian Post, US Planet, US Postnet, Japan Post, Dutch KIX Code, Intelligent Mail, British Post |

User Environment

| | |
|------------------------|---|
| Drop Specifications | Withstands multiple drops from 2.0m (6.6ft) to concrete |
| Environmental Sealing | IP65 |
| Operating Temperature | -10 °C to 50 °C (14 °F to 122 °F) |
| Storage Temperature | -40 °C to 70 °C (-40 °F to 158 °F) |
| Humidity | 5% to 95% relative humidity, non-condensing |
| Ambient Light Immunity | 0 ~ 100,000 lux |

Safety & Regulatory

| | |
|---------------------|--|
| EMC & Radio | CE, FCC, BSMI, RCM, KC, NCC, VCCI, MIC |
| Safety ² | LED Eye Safety IEC62471, Exempt Group |
| Environmental | Compliant with RoHS directive |

Accessories

| | |
|-------------------------|--|
| Smart Cradle | |
| RF Standard | Bluetooth v4.0 |
| Battery charging | Fast charge |
| User Interfaces | 1 blue link indicator, 2-color status indicator Beeper, Paging / Reset button |
| Host Interfaces | PS/2(DOS V) Keyboard Wedge, TTL RS232 Serial, USB HID, USB COM |
| Charging Cradle | |
| Battery charging | Fast charge |
| User interface | 1 blue power indicator |
| Host interface | USB |
| Interface Cables | PS/2(DOS V) Keyboard Wedge Cable RS232 Serial Cable USB Cable Micro USB Cable |

1. Reading range is measured under Cino's test conditions.

2. Do NOT stare into the LED beam.

